

Model C40 Brush Chipper will process branch and brushy material up to 178mm in diameter.

The powerful hydraulic feed system makes it easy to process any material. The 13" wide feed opening means bushy, twisted branches with forks are pulled into the


machine without effort. You simply control the feedrate with the control bar and the rest is automatic.

The draft action of the rotor will blow the chips into any size truck or stockpile on the ground. With the 360° rotating outlet chute the discharge direction can be changed within seconds.





Wide infeed opening – 330 x 178mm (13" x 7"). Excellent for foliage, brushy material and forked branches, reducing the number of saw cuts required.



Feed table - folds away and is locked when transporting the machine or when in operation.




Compact size yet efficient – low weight (800kg), and easy to maneuver.



Pivot & Swivel Outlet - adjustable deflector & 360 degree pivoting outlet chute. Pivot outlet vertically by 250mm. Positive locking, no tools required for adjustments.



Auto feed controller – monitors engine RPM and controls feed to suit. Operator adjustable by touch button. Auto reversing for quicker engine recovery. Feedroller jams are reversed and cleared automatically.



Quality construction – made of steel, CNC lasercut & folded – 100% accurate, durable hyperloc powder coated finish (Hansa green or optional colour of your choice).



Quality engine – great access for engine servicing – unhitch two rubber latches and engine cover pivots forward.



Hydraulic feed - quality hydraulic components, tidy design, in-feed speed is infinitely variable.



Brush Chipper Model C40



Light system – LED tail, brake and license plate lights, suitable for 12 or 24 volt system.



Quality output – chip size 10 – 20mm, great for use as a ground cover / mulch.



Vertical anvil – stones and grit fall between the end of the inlet and the blades resulting in reduced knife damage.



Blade access – loosen one bolt, pivot open the housing cover exposing the blades, adjustable to anvil after sharpening.



Feed roller – strong tension springs, pivot type feed-roller, operates with less friction, up to within 90mm of knives.



Simple controls – keystart, control panel with warning lights, manual throttle control, LCD screen displays engine RPM & hour meter.

SPECIFICATIONS		
Engine	Make & model	42HP Kohler Air Cooled
	Type of fuel	Diesel
General	Length	3200mm
	Width	1400mm
	Height	2200mm
	Weight	1000kg
Capacities	Fuel tank	45L
	Hydraulic oil tank	20L
Chassis	Frame description	100 x 50mm RHS
	Wheels	13" wheels
Cutting System	Disk speed	1800RPM
	Disk diameter	650mm x 25mm
	Shaft diameter	50mm
	Knives	Two
Feed System	Feed opening	330 x 178mm / 13" x 7"
	Chipping capacity	178mm / 7"
	Feed table height	750mm
	Feed table length (to feed rollers)	1550mm
	Infeed chute opening	960 x 650mm
	Roller Style	Single roller, spring mounted, 220mm / 8.7" diameter
	Feed Speed Range	0 - 40m/min / 0 - 135fpm infinitely variable, full reverse
Discharge System	Discharge Height	2200mm
	Degree of Rotation	360°
	Dogroo or riotation	
Brakes	Road brakes	Hydraulic road brakes with hand- brake standard







Please contact us for details if you are looking for a larger or smaller model. Visit our website for our full product range and videos of the machines in action.

MANUFACTURED BY:

Hansa Products Ltd - 36 Tawn Place, PO Box 10323, Hamilton 3200, New Zealand FREEPHONE 0508 4 HANSA (0508 442 672) PHONE 07 849 4749

FAX 07 849 4746 EMAIL info@hansaproducts.co.nz

www.hansaproducts.co.nz

Hansa Products has a policy of continuous improvement, therefore specifications may change without notice. All products come with a 12 month warranty, conditions apply.

