

MADE IN
NEW ZEALAND

Brush Chipper Model C60



Model C60 has a maximum branch capacity of 254mm (10 inch).

Its relatively light weight (1350kg) means the machine can be unhitched from the truck and pushed into confined areas where there is no vehicle access.

The powerful hydraulic feed system makes it easy to process any material. The 18" wide feed opening means bushy, twisted branches are pulled into the machine without effort. You simply control the feedrate with the control bar and the rest is automatic. With the 360° rotating swivel/pivot outlet chute the discharge direction & height can be changed within seconds.

FEATURES



Wide infeed opening – 457 x 254mm (18" x 10"). Excellent for foliage, brushy material and forked branches, reducing the number of saw cuts required.



Compact size yet efficient – low weight (1350kg), and easy to maneuver.



Auto feed controller – monitors engine RPM and controls feed to suit. Operator adjustable by touch button. Auto reversing for quicker engine recovery. Feedroller jams are reversed and cleared automatically.



Quality engine – 65HP Kohler, great access for engine servicing – unhitch two rubber latches and engine cover pivots forward.



Feed table – folds away and is locked when transporting the machine or when in operation.



Pivot & Swivel Outlet – adjustable deflector & 360 degree swivel outlet chute. Pivot outlet vertically by 250mm. Positive locking, no tools required for adjustments.



Quality construction – made of steel, CNC laser cut & folded – 100% accurate, durable hyperloc powder coated finish (Hansa green or optional colour of your choice).



Hydraulic feed – quality hydraulic components, tidy design, in-feed speed is infinitely variable.

The best chippers for any application.

Hansa[®]
CHIPPERS

Brush Chipper Model C60



Light system – LED tail, brake and license plate lights, suitable for 12 or 24 volt system.




Quality output – chip size 10 – 20mm, great for use as a ground cover / mulch.




Vertical anvil – stones and grit fall between the end of the inlet and the blades resulting in reduced knife damage.



Blade access – loosen one bolt, pivot open the housing cover exposing the blades, adjustable to anvil after sharpening.



Feed roller – strong tension springs, pivot type feed-roller, operates with less friction, up to within 90mm of knives.



Simple controls – key-start, control panel with warning lights, manual throttle control, LCD screen displays engine RPM & hour meter.

SPECIFICATIONS		
General	Length	3700mm
	Width	1750mm
	Height	2400mm
	Weight	1390kg
Engine	Make & model	65HP Kohler liquid cooled, 4 cylinder, turbo charged
	Type of fuel	Diesel
Capacities	Fuel tank	65L
	Hydraulic oil tank	24L
Chassis	Frame description	100 x 50 x 5mm RHS
	Wheels	14" wheels
Cutting System	Disk speed	1620RPM
	Disk diameter	800mm x 40mm
	Shaft diameter	60mm
	Knives	Four
Feed System	Feed opening	254 x 457mm / 10" x 18"
	Chipping capacity	254mm / 10"
	Feed table height	700mm
	Feed table length (to feed rollers)	1550mm
	Infeed chute opening	960 x 650mm
	Roller Style	Single roller, spring mounted, 300mm / 12" diameter
Discharge System	Feed Speed Range	40m/min / 135fpm, full reverse
	Discharge Height	2400mm
Brakes	Degree of Rotation	360°
	Road brakes	Hydraulic road brakes with hand-brake standard



Please contact us for details if you are looking for a larger or smaller model. Visit our website for our full product range and videos of the machines in action.

MANUFACTURED BY:

Hansa Products Ltd - 36 Tawn Place, PO Box 10323, Hamilton 3200, New Zealand

FREEPHONE 0508 4 HANSA (0508 442 672) PHONE 07 849 4749

FAX 07 849 4746 EMAIL info@hansaproducts.co.nz

www.hansaproducts.co.nz

Hansa Products has a policy of continuous improvement, therefore specifications may change without notice. All products come with a 12 month warranty, conditions apply.

The best chippers for any application.

Hansa[®]
CHIPPERS